

FEATURES

- An elegant and exquisite shutter manufactured skillfully from PVC and MDF composite material.
- Versatile range of louvers, frame styles and colors to complement any room décor
- Limited Specialty Shapes available.
- New PVC closed cell composite technology ensures superior strength and stiffness while remaining light-weight.
- Ruggedized cap stock enhances surface integrity; resists warping and twisting, heat and UV rays.
- Uniform, fade resistant color maintains consistent designer-quality look
- Easy low-cost maintenance perfect for today's busy lifestyles
- High thermal insulation value for superior energy efficiency
- Lanco's Lifetime Warranty

PRODUCT SPECIFICATIONS

Stile:	1 1/16" x 2" beaded
Top & Bottom Rail:	3/4" thick
Divider Rail:	3/4" thick; 2", 3" & 4"* wide Placed in panels over 72" high NB: Divider Rails are required in all Bi-Fold applications(26" max. width).
Louvers:	3/8" thick elliptical 2 1/2", 3 1/2" & 4 1/2"
Material:	PVC / MDF
Construction:	Mortise and Tennon joints
Tension System:	Adjustable tension screws
Tilt Rod:	1/2" thick, 5/8" wide
Louvers:	3/8" elliptical 2 1/2" and 3 1/2"
Hinge Mortise:	Non-mortise Hinges Hinges are placed 24" center to center maximum to influence swinging stability

RECOMMENDED PANEL WIDTH

	MINIMUM	MAXIMUM
2 1/2" LOUVERS	12	28" 32"***
3 1/2" LOUVERS	12	30" 36"***
4 1/2" LOUVERS	12	34" 36"***
		** WITH METAL INSERTED LOUVERS