

FEATURES

- Manufactured from the highest quality hardwoods (Basswood* and Poplar).
- Finished with high quality, American made, lacquer based finishes.
- Rigid birch wood dowel joinery ensures strength and stability.
- Installation friendly with pre-mitred frames featuring the Hoffman Dovetail Key Technology, as well as pre-installed magnets and hinges
- A functional choice of framing available
- Fully framed product with hinge finish choices.
- Available in white, Ten (10) standard off-whites and Ten (10) standard stains
- Shipped in Two (2) weeks: the most consistent and reliable delivery time in the industry
- Lifetime Limited Warranty demonstrates Lanco's commitment to quality.

* North American Basswood only for Stain

PRODUCT SPECIFICATIONS

Stile:	1 1/16" x 2" Beaded
Top & Bottom Rail:	7/8" thick, cut from 5" stock
Divider Rail:	7/8" thick; 2", 3" & 4"* wide *Placed in panels over 75" high
Louvers:	(3/8" thick); 2 1/2", 3 1/2" & 4 1/2"
Lumber:	Basswood or Poplar
Construction:	3" Dowels on 1 1/2" Centers
Tension System:	Adjustable tension screws
Tilt Rod:	1/2" thick, 5/8" wide
Hinge Mortise:	Non-mortise Hinges

RECOMMENDED PANEL WIDTH

	MINIMUM	MAXIMUM
2 1/2" LOUVERS	12	28"
3 1/2" LOUVERS	12	32"
4 1/2" LOUVERS	12	36"